

TURBINE INLET AIR COOLING (TIAC) COILS



PRECISE THERMODYNAMIC ANALYTICAL SOFTWARE

- Calculates lowest possible parasitic air pressure drop
- Guaranteed LAT precision to +0°C/-1°C
- Any working fluid

CUSTOMIZED PRECISION HEAT TRANSFER

- Corrosion resistant materials to match the operating environment
- Design solutions for either new build or retrofit
- Unique self-supporting coil casing design
- 304 stainless steel casing standard

INNOVATIVE OPTIONAL FEATURES

- Passive reheat to fix LAT @ <78% RH (NIL “wetting” of filter house elements)
- Integral stainless steel drainpan
- Integral mist eliminator
- Pre-filter module
- Inlet louvers

CRN



CASE STUDY
Griffith Energy Facility
Griffith, AZ



OWNER	PPL GLOBAL/DENA	GAS TURBINE MODEL	GE PG7241FA
PLANT EPC	BLACK AND VEATCH	GASTURBINENOMINALCAPACITY	170 MW
ON-LINE	2001	DESIGNINLETAIRTEMPERATURE	45° F
SYSTEM TYPE	SPC A - AMMONIA	GTIACREFRIGERATIONCAPACITY	9000 TR
GAS TURBINES	2	OVERALLPLANTENHANCEMENT	55 MW
NOMINALPLANTCAPACITY	520MW	AMBIENT AIR DESIGN	94° F DRY BULB 68° F WET BULB

CE(PED) Certification, UL508, ASME Sec. VIII, Canadian Registration Number, Canadian Standards Association



CRN



CSA

Colmac Coil Manufacturing, Inc. - World Headquarters & Research / Development Center

P.O. Box 571 • 370 N. Lincoln St. • Colville, WA 99114 USA

Phone: 509.684.2595 • Fax: 509.684.8331 • Website: www.colmaccoil.com

North American Headquarters

Colmac Coil Manufacturing, Inc.

P.O. Box 571

Colville, WA 99114

Midwest US Manufacturing

Colmac Coil Midwest

350 Baltimore Dr.

Paxton, IL 60957

"The Heat Transfer Experts"