HYGENAIR[™] A+H Hygienic Air Handling Unit



COLMA

8_

Manufacturing Inc.



COLMAC COIL MANUFACTURING, INC



The Heat Transfer Experts

Who We Are

Founded in 1971, Colmac Coil Manufacturing initially supplied heating and cooling coils to OEM customers and the HVAC industry. By the early 1980's Colmac Coil had expanded their refrigeration product line to include industrial air coolers and condensers for the ammonia refrigeration industry, developing a reputation for high quality products and the ability to engineer a wide range of heating and cooling solutions using their in-house developed heat and mass transfer modeling software.

Our Mission

The mission of Colmac Coil is to provide heat transfer markets worldwide with innovative. cost effective products that are configured, manufactured, and shipped with the shortest lead times in the industry, with fast, friendly service, for the mutual benefit of our employees, customers, and shareholders.

Our Products

- → Refrigeration Evaporators
- → Fluid Coolers & Condensers
- → Hygienic Air Handlers
- → Heating & Cooling Coils
- → Heat Pipes



Manufacturing Factory - Paxton, IL

Our Customers

Colmac Coil serves a wide variety of markets and customers with an emphasis in the following industries:

- → Industrial Refrigeration
- → HVAC
- → Power Generation
- → Process Cooling

HygenAir™ A+H Hygienic Air Handler Unit

Colmac Coil's Hygienic Air Handlers are custom engineered to help food processors maintain high quality and to meet the strict requirements of the USDA. A high level of food quality and safety can be achieved by controlling the process room air temperature, pressure, humidity, and cleanliness. Colmac Coil's Hygienic Air Handlers help manage these conditions by providing adequate cooling (and optional reheat for dehumidification), limiting air migration, managing condensation, and filtering out contaminants to deliver clean, sanitary air to the processing room environment.

Management of the **Processing Environment**

Temperature Management

Controlling the room air temperature is a key function Moisture in airstreams can result in condensation of the hygienic air handler. Colmac Coil has an when the airstream comes into contact with cold extensive history of being the premier manufacturer surfaces. Condensation droplets are generally known of evaporator coils for the industrial refrigeration to be possible sources of pathogen contamination and therefore it is important to minimize or eliminate markets. Manufacturing their own evaporator coils these droplets. Controlling the dew point of the air allows Colmac to offer a wide range of options when it comes to selecting the best evaporator in processing rooms will reduce the possibility of condensation occurring. With optional re-heat coils for the Hygienic Air Handler. Inline tube patterns, staggered tube patterns, various tube diameters and just downstream of the evaporator coils, Colmac fin thicknesses, as well as a full offering of special Coil's Hygienic Air Handler allows for proper humidity fin materials such as epoxy coated aluminum, antimanagement in the processing area. microbial fin, or even stainless-steel fins are available **Airborne Contaminate Management** for the evaporator coil construction.

Air Migration Management

Air movement between adjacent rooms can result in unwanted airborne contaminates in the processing areas. Colmac Coil's Hygienic Air Handlers have the ability to control the amount of outside, filtered air introduced into the space. With the ability to control the processing room air pressures to be slightly higher than adjacent rooms, the possibility of airborne crosscontamination is reduced.



Humidity Management

Proper filtration of the air in processing rooms is necessary to control airborne contaminates. Colmac Coil's Hygienic Air Handler is supplied with high efficiency extended surface filters with various filter efficiency ratings from MERV 11 up to HEPA H14.



HygenAir™ Features A+H Hygienic Air Handler Unit

Designed to improve the process and packaging room environment, the Colmac Coil Hygienic Air Handler is manufactured with hygienic welds and coil construction materials.

Colmac Coil proprietary selection software gives you the ability to select custom sizes and options that's optimal for the system type and processing environment conditions.

- → Available For All System Types
- → Customized Configurations
- → Hygienic Design
- → Low Maintenance



- Electronically commuted, direct drive fans are standard, for units up to 40,000 cfm
- Built in fan speed control
- Ingress protection rating of IP55
- · Corrosion resistant construction
- High reliability and long life
- Extremely low sound levels
- Large airflow capacities
- Plug & play fan-motor bell mouth assembly



 Includes burner startup, shutdown, and safety monitoring

02

- Local temperature control and operator interface
- RTD inputs for control and high temperature limit



- Allen Bradley Compact Logix PLC System with Ethernet Communication
- Panel View Plus 7 with 6-inch display mounted on face of main control panel
- VFD controls for both supply and exhaust fans
- Fused disconnects(s)

COLMAC

03

2

....

....

- Outside air and re-circulated air controls for a fixed amount of outside air
- Optional economizer mode
- Optional room pressure control



- Standard G235 galvanized steel interior and exterior walls
- · Optional 304 stainless steel interior
- All wall joints are sealed with food grade sealant
- Standard 2" thick fiberglass insulation enclosed in wall panels



 Access doors are included for easy access to all compartments



05



- Fully welded steel frame
- Fully insulated floor/base with polyurethane spray foam for thermal / vapor barrier
- Fiberglass insulation enclosed in wall panels
- Lifting lugs for crane rigging

The Colmac Advantage

Manufacturing our own evaporator coils allows us to offer a wide range of options when it comes to selecting the best evaporator for the hygienic air handler.

HygenAir™ **Features**

A+H Hygienic Air Handling Unit



- Standard stainless-steel tube/ aluminum fin construction. Other fin/ tube materials are available to meet the requirements of every application
- Optional epoxy coated fins
- Optional inline tube coils for ease of cleaning / sanitation
- Coils are designed and manufactured by Colmac Coil, as per the requirements of ASME B31.5



- Dual pitch drain pan ensures complete liquid drainage
- Full coverage drain pans for entire unit interior
- Standard construction is 304 stainless steel

• Fully welded drain pans with hygienic weld finish options

Start up Support

Our commitment to your project goes beyond the design, value engineering, custom manufacturing, and other project support we provide. Upon request, a Colmac Coil technician is sent to each jobsite to program the controls ensuring the hygienic unit is optimized to each application.



- Available in various ratings from MERV 11 to HEPA 13
- MERV 11 to 16 are AAF VariCel, High **Efficiency Supported Pleat Filters**
- Excellent performance in difficult operating conditions
- Lightweight and easy to install
- Fully resistant to corrosive environments
- Optional extra set of final filters



Plenum fans with direct drive motors

- Non-overloading, single thickness, airfoil type impeller
- Motor base is upgradeable to fully welded, hygienic design
- TEFC, premium efficiency motors are standard
- Full VFD control is included









 Low leakage air-foil control damper All aluminum construction with stainless steel trim Standard modulating NEMA 4 actuators with position feedback



- AAF PerfectPleat, MERV 8, Extended Surface Pleated Panel Filter
- Mechanical efficiency does not rely on electric charge technology
- Self-supporting media made from virgin fiber – no wire support needed
- · Consistent media with controlled fiber size and blend
- Environmentally friendly no dyes, no metal, full incinerable
- Optional extra set of pre filters



- Low leakage air-foil control damper
- · All aluminum construction with stainless steel trim
- Standard modulating NEMA 4 actuators with position feedback



Heating Options

- Direct fired propane or natural gas burner designed for 80 degree F temperature rise
- Optional steam or hot water heating coils

Optional Features



Production Mode

Clean-Up Mode

for control of the process room environment.

Economizer

During certain times of the year, outside air temperatures are low enough to where the mechanical cooling functions can be reduced or eliminated, thereby saving compressor energy. Colmac Coil's Hygienic Air Handlers, when equipped with the optional economizer function, can automatically transition to economizer mode.

Sequential Defrost

When process room temperatures are low enough to result in frosted fins on the evaporator coil, Colmac Coil's Hygienic Air Handler can be provided with sequentially defrosted evaporator coils. To defrost, the suction pressure of one evaporator is raised, where the process air melts the accumulated frost.

Additional Options

- → Return-air drop boxes and return drip pans
- → Dwyer 605 filter gauge with PLC communication
- \rightarrow Upgrade to 10" display for Allen Bradley Panel View Plus
- → Supply-Air Diffusers

- → SS NEMA 4X remote panel with panel view (6")
- → Room pressure control
- → Shrink wrap packaging on select unit models
- → SST interior with caulked joints
- → Unit mounted smoke detector

- → Sequential defrost
- → Motor service rails
- → Flooded-surge vessels
- → HEPA filters

→ Reheat coils

Colmac Coil Manufacturing, Inc. | www.colmaccoil.com Colmac Coil Manufacturing, Inc. | www.colmaccoil.com





During production mode, Colmac Coil's Hygienic Air Handler mixes fresh air in small guantities with the process room air to provide positive air pressure in the space. This additional air makes up for the air that is spilling from the processing space through doors, openings, or exhaust fans. Providing outside air allows users to control the air migration movement between rooms. The mixed air is filtered to capture airborne contaminates, before entering the fan section where plenum fans are utilized to circulate the process room air. Each plenum fan is a VFD controlled direct drive, backward curved, high efficiency airfoil impeller, that guietly and efficiently delivers the necessary air volume at high static pressures. A hygienic design is accomplished with an optional, completely cleanable, fully welded motor base. Final filters capture particles as small as 0.3 microns before the Hygienic Air Handler delivers high quality air to the production space via diffusers or ductwork. Exhaust fans positioned in the return airstream allow for precise control of the room air pressure, which allows for effective air migration management. Colmac Coil's Hygienic Air Handlers are controlled via an Allen Bradley Compact Logix PLC system with ethernet communication. A Panel View Plus 7 display mounted on the face of the main control panel allows

During clean-up mode, Colmac Coil's Hygienic Air Handler draws 100% fresh air from outside, where it is conditioned (dried) in order to maximize moisture collection from the room environment. Upon returning to the Hygienic Air Handler, powerful exhaust fans expel the moisture laden air to the outdoors. Depending on the outside air temperature and humidity, either mechanical cooling or heating is automatically utilized in order to provide guick moisture removal from the processing space.

Selection Software



Colmac Coil's Hygienic Air Handler selection software is a web-based program that allows you to design a customized unit to the specifications needed for your project. The software guides the design based off the room inputs of the processing room environment. As you make the equipment selections, the software instantly provides the engineer unit specifications, a price summary report, a design data sheet, and pricing details for the the hygienic air handler unit.

Selection Software Features:

- Web based program
- Generate project reports in a variety of file formats
- Unit specification documents
 - Price summaries
 - Engineering schedules
 - Engineering specifications

Contact Us Today

We look forward to finding a solution with you. To learn more, receive a quote, or sign up for selection software, visit www.colmaccoil.com to contact your local Colmac Coil sales office or the factory.

Increase Hygiene In The Processing Space















Ice Cream Processing Room







| MODEL | Airflow (CFM) | EST. Weight (LB) | А | В | С | D | Е | F | G | н | J | к |
|-------|------------------|---------------------|-----|-----|-----|-----|----|-----|----|-----|-----|-----|
| A+H6 | 6000 | 10500 | 262 | 74 | 80 | 48 | 36 | 30 | 24 | N/A | N/A | N/A |
| A+H12 | 12000 | 13000 | 274 | 84 | 82 | 72 | 60 | 60 | 24 | N/A | N/A | N/A |
| A+H18 | 18000 | 15500 | 282 | 95 | 92 | 72 | 60 | 72 | 30 | N/A | N/A | N/A |
| A+H22 | 22000 | 16500 | 296 | 95 | 108 | 72 | 72 | 72 | 36 | N/A | N/A | N/A |
| A+H30 | 30000 | 23000 | 337 | 129 | 102 | 108 | 72 | 96 | 36 | 101 | 140 | 96 |
| A+H40 | 40000 | 24000 | 337 | 129 | 126 | 108 | 96 | 96 | 48 | 101 | 140 | 96 |
| A+H52 | 52000 | 31500 | 337 | 167 | 130 | 132 | 96 | 132 | 48 | 101 | 140 | 96 |
| A+H70 | 65000 | 37500 | 337 | 188 | 137 | 156 | 96 | 160 | 48 | 101 | 140 | 96 |

Standard Unit Dimensions

QUALITY PRODUCTS FROM COLMAC COIL



Manufacturing Inc.



www.colmaccoil.com "The Heat Transfer Experts" Since 1971

North American Headquarters

Colmac Coil Manufacturing, Inc. 370 N. Lincoln St. | P.O. Box 571 Colville, WA 99114 | USA +1.509.684.2595 | +1.800.845.6778

Midwest US Manufacturing

Colmac Coil Midwest 350 Baltimore Dr. Paxton, IL 60957 | USA



ASME Sec. VIII, Canadian Registration Number, UL508, Canadian Standards Association

©2023 Colmac Coil Manufacturing, Inc.